LASERTECH®
industrial laser pointers

# Compact and powerful red light emitter for marking cutting lines and many other optical projections - Series LT1S20



## M4330A2VX0

**Type of projection:** Cross
**Wavelength:** 635 nm (bright red)
**Max output power:** 30 mW
**Supply voltage:** 5 Vdc
**Protection class:** IP67

## TECHNICAL DETAILS

| | |
|---|---|
| **Code** | M4330A2VX0 |
| **Light source** | Laser diode |
| **Type of projection** | Cross |
| **Wavelength** | 635 nm (bright red) |
| **Max output power** | 30 mW |
| **Supply voltage** | 5 Vdc |
| **Operating current** | <120 mA |
| **Connection** | Cable 2x0,25 cm 200 |
| **Casing** | Green anod.alum. |
| **Dimension** | 20x130 mm |
| **Protection class** | IP67 |
| **Laser class** | 2M |
| **Storage temperature °C/°F** | -40 +85 °C / -40 +185 °F |
| **Operating temperature °C/°F** | -10 +50 °C / 14 +122 °F |
| **Application sector** | Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc. |
| **Color** | Bright red |
| **Note** | For better use you have to specify the focus distance. If not specified, emitter is focused for mm 2000. The cross (spread 10°) has a total wide of mm 160 at a distance of mm 1000 from the emission point, perpendicularly to laser beam. Cross lenses with spread 2°, 5°, 10°, 25°, 30°, 45°, 75° available. .Other optical projections available on request |

## RELATED ACCESSORIES

- Stabilized power supplier, input 8-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

Lasertech | MEC AROUND S.r.l.
Via Mortalas, 15 Z.I. - 33080 Orcenico Inferiore Zoppola (PN)-ITALY
Tel. +39 0434 977335 - info@lasertech.it - www.lasertech.it

Lasertech | MEC AROUND S.r.l.
Via Mortalas, 15 Z.I. - 33080 Orcenico Inferiore Zoppola (PN)-ITALY
Tel. +39 0434 977335 - info@lasertech.it - www.lasertech.it