

Compact and powerful green light emitter for marking cutting lines and many other optical projections - Series LT2V20



M4V01B4VL0

Type of projection: Line

Wavelength: 520 nm (bright green)

Max output power: 1 mW

Supply voltage: 9-36 Vdc 10-30 Vac

Protection class: IP67

TECHNICAL DETAILS

Code	M4V01B4VL0
Light source	Laser diode
Type of projection	Line
Wavelength	520 nm (bright green)
Max output power	1 mW
Supply voltage	9-36 Vdc 10-30 Vac
Operating current	<90 mA
Connection	M12 connector + cm 500 cable
Casing	Green anod.alum.
Dimension	20x145 mm
Linelength	Max 2,5mt
Protection class	IP67
Laser class	2
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-20 +60 °C / -4 +140 °F
Application sector	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
Color	Bright green
Note	For better use you have to specify the focus distance. If not specified, emitter is focused for infinity. Line lenses with spread 5°, 20°, 30°, 45°, 90° available. The line has a wide, at a distance of mm 1000 from the emission point and perpendicularly to laser beam, as it follows: 05° spread = mm 70 ; 20° spread = mm 310 ; 30° spread = mm 660 ; 45° spread = 800mm; 90° spread = mm 1800. You have to specify the spread that you wish. If not specified, emitter is shipped with a 90° spread lens. The visibility and the lenght of the line depend on the mounting of the laser and the brightness of the enviroment.Other optical projections available on request

RELATED ACCESSORIES

- Stabilized power supplier input 100-240Vac, output 24Vdc, 1,25A, 2 poles 10A plug
- Stabilized power supplier input 100-240Vdc, output 24Vdc, 1A, DIN attachment
- Dimming flap 20 mm diam, black
- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

LASERTECH®

— industrial laser pointers —