

Compact and powerful green light emitter for marking cutting lines and many other optical projections - Series LT2V20



M4V05B4V00

Type of projection: Dot

Wavelength: 520 nm (bright green)

Max output power: 5 mW

Supply voltage: 9-36 Vdc 10-30 Vac

Protection class: IP67

TECHNICAL DETAILS

Code	M4V05B4V00
Light source	Laser diode
Type of projection	Dot
Wavelength	520 nm (bright green)
Max output power	5 mW
Supply voltage	9-36 Vdc 10-30 Vac
Operating current	<90 mA
Connection	M12 connector + cm 500 cable
Casing	Green anod.alum.
Dimension	20x145 mm
Protection class	IP67
Laser class	3R
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-20 +60 °C / -4 +140 °F
Application sector	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
Color	Bright green
Note	For better use you have to specify the focus distance. If not specified, emitter is focused for mm 2000 .Other optical projections available on request

RELATED ACCESSORIES

- Stabilized power supplier input 100-240Vac, output 24Vdc, 1,25A, 2 poles 10A plug
- Stabilized power supplier input 100-240Vdc, output 24Vdc, 1A, DIN attachment
- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

LASERTECH®

— industrial laser pointers —