LASERTECH®
industrial laser pointers

Versatile point, cross, line, circle emitter with M8 connector - Series LT2S



N3501HBVC0

Type of projection: Circle
Wavelength: 650 nm (red)
Max output power: 1 mW
Supply voltage: 5-30 Vdc
Protection class: IP64

TECHNICAL DETAILS

Code	N3501HBVC0
Light source	Laser diode
Type of projection	Circle
Wavelength	650 nm (red)
Max output power	1 mW
Supply voltage	5-30 Vdc
Operating current	<40 mA
Connection	M8 connector + cm 300 cable
Casing	Green anod.alum.
Dimension	14x95 mm
Protection class	IP64
Laser class	2
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-10 +50 °C / 14 +140 °F
Application sector	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
Color	Red
Note	For better use you have to specify the focus distance. If not specified, emitter is focused for mm 2000. The circle (spread 3°) has a central dot and a diameter of mm 40 at a distance of mm 1000 from the emission point. Circle lenses with spread 3°, 4°, 34°, 45° available. .Other optical projections available on request

RELATED ACCESSORIES

- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier, input 8-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Reclining bracket for 14 mm diam module, black
- Ball-shaped head bracket for 14 mm diam module, black
- Reduction bush for 14 mm diam module, black

Lasertech | MEC AROUND S.r.l.
Via Mortalas, 15 Z.I. - 33080 Orcenico Inferiore Zoppola (PN)-ITALY
Tel. +39 0434 977335 - info@lasertech.it - www.lasertech.it

Lasertech | MEC AROUND S.r.l.
Via Mortalas, 15 Z.I. - 33080 Orcenico Inferiore Zoppola (PN)-ITALY
Tel. +39 0434 977335 - info@lasertech.it - www.lasertech.it