LASERTECH®
industrial laser pointers

# Battery powered point, cross, line, circle emitter - Series LT2B20



## N6503EXVL0

**Type of projection:** Line
**Wavelength:** 650 nm (red)
**Max output power:** 3 mW
**Supply voltage:** Battery 3Vdc type CR123A
**Protection class:** IP64

## TECHNICAL DETAILS

| | |
|---|---|
| **Code** | N6503EXVL0 |
| **Light source** | Laser diode |
| **Type of projection** | Line |
| **Wavelength** | 650 nm (red) |
| **Max output power** | 3 mW |
| **Connection** | Cableless |
| **Casing** | Green anod.alum. |
| **Linelength** | Max 1,5mt |
| **Protection class** | IP64 |
| **Laser class** | 2M |
| **Storage temperature °C/°F** | -40 +85 °C / -40 +185 °F |
| **Operating temperature °C/°F** | -10 +50 °C / 14 +140 °F |
| **Application sector** | Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc. |
| **Color** | Red |
| **Supply voltage** | Battery 3Vdc type CR123A |
| **Operating current** | <100 mA |
| **Dimension** | 20x135 mm |
| **Note** | Operating time for a battery: approx 14 hours. Line lenses with spread 5°, 20°, 30°, 45°, 90° available. The line has a wide, at a distance of mm 1000 from the emission point and perpendicularly to laser beam, as it follows: 05° spread = mm 70 ; 20° spread = mm 310 ; 30° spread = mm 660 ; 45° spread = 800mm; 90° spread = mm 1800. You have to specify the spread that you wish. If not specified, emitter is shipped with a 90° spread lens. The visibility and the lenght of the line depend on the mounting of the laser and the brightness of the enviroment.Other optical projections available on request |

## RELATED ACCESSORIES

- Dimming flap 20 mm diam, black
- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

Lasertech | MEC AROUND S.r.l.
Via Mortalas, 15 Z.I. - 33080 Orcenico Inferiore Zoppola (PN)-ITALY
Tel. +39 0434 977335 - info@lasertech.it - www.lasertech.it

Lasertech | MEC AROUND S.r.l.
Via Mortalas, 15 Z.I. - 33080 Orcenico Inferiore Zoppola (PN)-ITALY
Tel. +39 0434 977335 - info@lasertech.it - www.lasertech.it